

Table 4.1 Thread Operation Latencies (μ s) [ANDE92]

Operation	User-Level Threads	Kernel-Level Threads	Processes
Null Fork	34	948	11,300
Signal Wait	37	441	1,840

Table 4.2 Relationship Between Threads and Processes

Threads:Processes	Description	Example Systems
1:1	Each thread of execution is a unique process with its own address space and resources.	Traditional UNIX implementations
M:1	A process defines an address space and dynamic resource ownership. Multiple threads may be created and executed within that process.	Windows NT, Solaris, Linux OS/2, OS/390, MACH
1:M	A thread may migrate from one process environment to another. This allows a thread to be easily moved among distinct systems.	Ra (Clouds), Emerald
M:N	Combines attributes of M:1 and 1:M cases.	TRIX

Table 4.3 Windows 2000 Process Object Attributes

Process ID	A unique value that identifies the process to the operating system.
Security Descriptor	Describes who created an object, who can gain access to or use the object, and who is denied access to the object.
Base priority	A baseline execution priority for the process's threads.
Default processor affinity	The default set of processors on which the process's threads can run.
Quota limits	The maximum amount of paged and nonpaged system memory, paging file space, and processor time a user's processes can use.
Execution time	The total amount of time all threads in the process have executed.
I/O counters	Variables that record the number and type of I/O operations that the process's threads have performed.
VM operation counters	Variables that record the number and types of virtual memory operations that the process's threads have performed.
Exception/debugging ports	Interprocess communication channels to which the process manager sends a message when one of the process's threads causes an exception.
Exit status	The reason for a process's termination.

Table 4.4 Windows 2000 Thread Object Attributes

Thread ID	A unique value that identifies a thread when it calls a server.
Thread context	The set of register values and other volatile data that defines the execution state of a thread.
Dynamic priority	The thread's execution priority at any given moment.
Base priority	The lower limit of the thread's dynamic priority.
Thread processor affinity	The set of processors on which the thread can run, which is a subset or all of the processor affinity of the thread's process.
Thread execution time	The cumulative amount of time a thread has executed in user mode and in kernel mode.
Alert status	A flag that indicates whether the thread should execute an asynchronous procedure call.
Suspension count	The number of times the thread's execution has been suspended without being resumed.
Impersonation token	A temporary access token allowing a thread to perform operations on behalf of another process (used by subsystems).
Termination port	An interprocess communication channel to which the process manager sends a message when the thread terminates (used by subsystems).
Thread exit status	The reason for a thread's termination.