

Superscalar Processors

Ch 14

Limitations, Hazards
 Instruction Issue Policy
 Register Renaming
 Branch Prediction
 PowerPC, Pentium 4

New dependency for superscalar case? ⁽⁸⁾

- Name dependency (nimiriippuvuus)
 - two instructions use the same data item
 - register or in memory
 - no value passed from one instruction to another
 - instructions have all their correct data available
 - each individual result is the one intended
 - overall result is not the one intended
 - two cases: Output Dependency & Antidependency
 - (kirjoitusriippuvuus?) (antiriippuvuus)
 - examples on next 2 slides
 - what if there are aliases?
 - E.g., two registers point to same physical address

Superscalar Processing ⁽⁵⁾

- Basic idea: more than one instruction completion per cycle
- Aimed at speeding up scalar processing
 - use many pipelines and not just more pipeline phases (Fig. 14.2 (Fig. 13.2 [Stal99]))
- Many instructions in execution phase simultaneously
 - need parallelism also in earlier & later phases
 - may not execute (completely) in given order (Fig. 13.1 [Stal99])
- Multiple pipelines
 - question: when can instruction be executed? (Fig. 14.1)
- Fetch many instructions at the same time
 - memory access must not be bottleneck

Output Dependency?

- Some earlier instruction has not yet finished writing from the same location (register) that we want to write to
 - execution time semantics determined by the original order of machine instructions
- Need to preserve order

```
read  r1, X
add   r2, r1, r3
add   r1, r4, r5
```

Want to have sum of r4 and r5 in r1 after all these three instructions were executed (not value of variable X)

Why couldn't we execute this instruction right now? ⁽⁴⁾

- (True) Data Dependency (datariippuvuus)
 - load r4, salary(r6)
 - mul r2, r4, r10
- Procedural or Control Dependency (kontrolliriippuvuus)
 - even more costlier than with normal pipeline
 - now may waste more than one instruction!
- Resource Conflict (resurssikonflikti)
 - there is no available circuit right now
 - memory buffer, FP adder, register file port
- Usual solution: circuits to detect problem and stall pipeline when needed

Antidependency

Some earlier instruction has not yet finished reading from the same location that we want to write to
 Need to preserve order

```
mv r2, r1
add r1, r4, r5
```

Want to have original value of r1 in r2

Machine Parallelism (2)

- Instruction-level parallelism (ILP)
 - How much parallelism is there
 - Theoretical maximum
- Machine parallelism
 - How much parallelism is achieved by any specific machine or architecture?
 - At most as much as instruction-level parallelism
 - dependencies?
 - physical resources?
 - not optimized (I.e., stupid?) design?

6.10.2003

Copyright Teemu Kerola 2003

7

Window of Execution

Fig. 14.6

(Fig. 13.6 [Stal99])

- Bigger is better
 - easier to find a good candidate that can be issued right now
 - more work to figure out all dependencies
 - too small value will limit machine parallelism significantly
 - E.g., 6th instruction could be issued, but only 4 next ones are even considered

6.10.2003

Copyright Teemu Kerola 2003

10

Superscalar Processor (4)

- Instruction dispatch Fig. 14.6
 - get next available executable instruction from instruction stream (Fig. 13.6 [Stal99])
- Window of execution
 - all instructions that are considered to be issued
- Instruction issue
 - allow instruction to start execution
 - execution and completion phase should continue now with no stalls
 - if any stalls needed, do them before issue
- Instruction reorder and commit (retiring)
 - hopefully all system state changes here!
 - last chance to change order or abandon results

6.10.2003

Copyright Teemu Kerola 2003

8

Instruction Issue (3)

Fig. 14.6

(Fig. 13.6 [Stal99])

- Select next instruction(s) for execution
- Check first everything so that execution can proceed with no stalls (stopping) to the end
 - resource conflicts
 - data dependencies
 - control dependencies
 - output dependencies
 - antidependencies
- Simpler instruction execution pipelines
 - no need to check for dependencies

”data in R4 is not yet there, but it will be there in three cycles when it is needed by this instruction”

6.10.2003

Copyright Teemu Kerola 2003

11

Instruction Dispatch (7)

Fig. 14.6

(Fig. 13.6 [Stal99])

- Whenever there are both
 - available slots in window of execution
 - ready instructions from prefetch or branch prediction buffer
 - instructions that do not need to stall at all during execution
 - all dependencies do not need to be solved yet

6.10.2003

Copyright Teemu Kerola 2003

9

Instruction Issue Policies (3)

- Instruction fetch policy
 - constraints on how many instructions are considered to be dispatched at a time
 - E.g., 2 instructions fetched and decoded at a time
⇒ both must be dispatched before next 2 fetched
- Instruction execution policy
 - constraints on which order dispatched instructions may start execution
- Completion policy
 - constraints the order of completions

6.10.2003

Copyright Teemu Kerola 2003

12

Example 1 of Issue Policy (7)

- In-order issue with in-order completion
 - same as purely sequential execution (Fig. 14.4 (a))
 - no instruction window needed (Fig. 13.4 (a) [Stal99])
 - instruction issued only in original order
 - many can be issued at the same time
 - instructions completed only in original order
 - many can be completed at the same time
 - check before issue:
 - resource conflicts, data & control dependencies
 - execution time, so that completions occur in order: wait long enough that earlier instructions will complete first
 - Pentium II: out-of-order middle execution for micro-ops (μ ops) with in-order completion

6.10.2003

Copyright Teemu Kerola 2003

13

Get Rid of Name Dependencies (3)

- Problem: independent data stored in locations with the same name
 - often a storage conflict: same register used for two different purposes
 - results in wait stages (pipeline stalls, “bubbles”)
- Cure: register renaming
 - actual registers may be different than named registers
 - actual registers allocated dynamically to named registers
 - allocate them so that name dependencies are avoided
- Cost:
 - more registers
 - circuits to allocate and keep track of actual registers

6.10.2003

Copyright Teemu Kerola 2003

16

Example 2 of Issue Policy (5)

- In-order issue with out-of-order completion
 - issue in original order
 - many can be issued at the same time (Fig. 14.4 (b))
 - no instruction window needed (Fig. 13.4 (b) [Stal99])
 - allow executions complete before those of earlier instructions
 - check before issue:
 - resource conflicts, data & control dependencies
 - output dependencies: wait long enough to solve them

6.10.2003

Copyright Teemu Kerola 2003

14

Register Renaming (3)

Output dependency: I3 can not complete before I1 has completed first:

Antidependency: I3 can not complete before I2 has read value from R3:

Rename data in register R3 to actual hardware registers R3a, R3b, R3c

Rename also other registers: R4b, R5a, R7b

No name dependencies now:

R3:=R3 + R5;	(I1)
R4:=R3 + 1;	(I2)
R3:=R5 + 1;	(I3)
R7:=R3 + R4;	(I4)
R3b:=R3a + R5a	(I1)
R4b:=R3b + 1	(I2)
R3c:=R5a + 1	(I3)
R7b:=R3c + R4b	(I4)

- Drawback: need more registers
 - Pentium II: 40 extra regs + 16 normal regs
- Why R3a & R3b?

6.10.2003

Copyright Teemu Kerola 2003

17

Example 3 of Issue Policy (5)

- Out-of-order issue with out-of-order completion
 - issue in any order (Fig. 13.4 (c) [Stal99])
 - many can be issued at the same time (Fig. 14.4 (c))
 - instruction window for dynamic instruction scheduling
 - allow executions complete before those of earlier instructions
 - Check before issue:
 - resource conflicts, data & control dependencies
 - output dependencies: wait for earlier instructions to write their results before we overwrite them
 - antidependencies: wait for earlier instructions issued later to pick up arguments before overwriting them

The real superscalar processor

6.10.2003

Copyright Teemu Kerola 2003

15

Superscalar Implementation (7)

- Fetch strategy (Fig. 14.6)
 - prefetch, branch prediction (Fig. 13.6 [Stal99])
- Dependency check logic
- Forwarding circuits (shortcuts) to transfer dependency data directly instead via registers or memory (to get data accessible earlier)
- Multiple functional units (pipelines)
- Effective memory hierarchy to service many memory accesses simultaneously
- Logic to issue multiple instruction simultaneously
- Logic to commit instruction in correct order

6.10.2003

Copyright Teemu Kerola 2003

18

Overall Gain from Superscalar Implementation

- "Base" machine, starting point for comparison
 - out-of-order issue
- See the effect of ...
 - renaming ⇒ right graph (Fig. 13.5 [Stal99])
 - issue window size ⇒ color of vertical bar (Fig. 14.5)
 - duplicated
 - data cache access ⇒ "+ld/st"
 - ALU ⇒ "ALU"
 - both ⇒ "both"
- Max speed-up about 4

6.10.2003

Copyright Teemu Kerola 2003

19

PowerPC 601 Pipelines (4)

- Instruction pipelines (Fig. 13.12 [Stal99])
 - all state changes in final "Write Back" phase (Fig. 14.12)
 - up to 3 instruction can be dispatched at the same time, and issued right after that in each pipeline if no dependencies exist
 - dependencies solved by stalls
 - ALU ops place their result in one of 8 condition code field in condition register
 - up to 8 separate conditions active concurrently

6.10.2003

Copyright Teemu Kerola 2003

22

PowerPC 601 Branches (4)

- Zero cycle branches
 - branch target addresses computed already in lower dispatch buffers
 - before dispatch or issue!
 - Easy: unconditional branches (jumps) or branch on already resolved condition code field
 - otherwise
 - conditional branch backward: guess taken
 - conditional branch forward: guess not taken
 - if speculation ends up wrong, cancel conditional instructions in pipeline before write-back
 - speculate only on one branch at a time

6.10.2003

Copyright Teemu Kerola 2003

20

6.10.2003

Copyright Teemu Kerola 2003

23

Example: PowerPC 601 Architecture (2)

- General RISC organization
 - instruction formats (Fig. 11.9) (Fig. 10.9 [Stal99])
 - 3 execution units (Fig. 14.10) (Fig. 13.10 [Stal99])
- Logical view (Fig. 14.11) (Fig. 13.11 [Stal99])
 - 4 instruction window for issue
 - each execution unit picks up next one for it whenever there is room for new instruction
 - integer instructions issued only when 1st (dispatch buffer 0) in queue

6.10.2003

Copyright Teemu Kerola 2003

21

PowerPC 601 Example

- Conditional branch example
 - Original C code (Fig. 14.13 (a)) (Fig. 13.13 [Stal99])
 - Assembly code (Fig. 14.13 (b))
 - predict branch not taken
 - Correct branch prediction (Fig. 13.14 [Stal99]) (Fig. 14.14 (a))
 - Incorrect branch prediction (Fig. 14.14 (b))

6.10.2003

Copyright Teemu Kerola 2003

24

PowerPC 620 Architecture

- 6 execution units
- Up to 4 instructions dispatched simultaneously
- Reservation stations to store dispatched instructions and their arguments
 - kind of rename registers also!

[HePa96] Fig. 4.49

PowerPC 620 Rename Registers (7)

- Rename registers to store results not yet committed
 - normal uncompleted and speculative instructions
 - 8 int and 12 FP extra rename registers
 - in same register file as normal registers
 - results copied to normal registers at commit
 - information on what to do at commit is in completion unit in reorder buffers
- Instruction completes (commits) from completion unit reorder buffer once all previous instructions are committed
 - max 4 instructions can commit at a time

[HePa96] Fig. 4.49

Intel Pentium II speculation

- 512-entry branch target buffer
 - 4-bit prediction state, 4-way set-associative
- Static prediction
 - used before dynamic will work
 - forward "not taken", backward "taken"
- In-order-completion for 40 μ ops (micro-operations) limits speculation
- 4-entry Return Stack Buffer (RSB)
 - return addresses are often found quickly without accessing Activation Record Stack

PowerPC 620 Speculation

- Speculation on branches
 - 256-entry branch target buffer
 - two-way set-associative
 - 2048-entry branch history table
 - used when branch target buffer misses
 - speculation on max 4 unresolved branches

