com.javaexchange.dbConnectionBroker

Class HttpServletJXGB

```
java.lang.Object
  |
  +--javax.servlet.GenericServlet
        |
        +--javax.servlet.http.HttpServlet
              |
              +--com.javaexchange.dbConnectionBroker.HttpServletJXGB
```

public class **HttpServletJXGB**
extends javax.servlet.http.HttpServlet

Creates a two-tier database connection pool that can be shared by many servlets through inheritance.

Version:
2.0.0 7/28/99

Author:
Marc A. Mnich

See Also:
Serialized Form

Field Summary

protected static com.javaexchange.dbConnectionBroker.DbConnectionBroker	**myBroker**
protected static int	**servletInits**

Fields inherited from class javax.servlet.GenericServlet
config

Constructor Summary

HttpServletJXGB()	

Method Summary

void	**init**(javax.servlet.ServletConfig config)

Methods inherited from class javax.servlet.http.HttpServlet

doDelete, doGet, doHead, doOptions, doPost, doPut, doTrace, getAllDeclaredMethods, getLastModified, maybeSetLastModified, service, service

Methods inherited from class javax.servlet.GenericServlet

destroy, getInitParameter, getInitParameterNames, getServletConfig, getServletContext, getServletInfo, log

Methods inherited from class java.lang.Object

, clone, equals, finalize, getClass, hashCode, notify, notifyAll, registerNatives, toString, wait, wait, wait

Field Detail

myBroker

protected static com.javaexchange.dbConnectionBroker.DbConnectionBroker **myBroker**

---

servletInits

protected static int **servletInits**

Constructor Detail

HttpServletJXGB

```
public HttpServletJXGB()
```

Method Detail

init

```
public void init(javax.servlet.ServletConfig config)
          throws javax.servlet.ServletException
```

Overrides:

init in class javax.servlet.GenericServlet