

# Overview of the INEX 2007 Book Search Track (BookSearch'07)

Gabriella Kazai<sup>1</sup> and Antoine Doucet<sup>2</sup>

<sup>1</sup> Microsoft Research Cambridge, United Kingdom

[gabkaz@microsoft.com](mailto:gabkaz@microsoft.com)

<sup>2</sup> University of Caen, France

[doucet@info.unicaen.fr](mailto:doucet@info.unicaen.fr)

**Abstract.** This paper provides an overview of the newly launched Book Search Track at INEX 2007, its participants, the tasks, the book corpus, test topics and relevance assessments, as well as some results.

## 1 Introduction

Libraries around the world and commercial companies like Amazon, Google and Microsoft are digitizing thousands upon thousands of books in an effort to enable online access to these collections. The Open Content Alliance (OCA)<sup>3</sup>, a library initiative formed after Google announced its library book digitization project, has brought digitization projects into the public eye, even though libraries have been driving digitization efforts for decades before that. Unlike library digitization projects, which are centered around preservation and involve the careful and individual selection of materials to be digitized, mass-digitization efforts aim at the conversion of materials on an industrial scale with minimum human intervention [2].

The increasing availability of the full-text of digitized books on the Web and in digital libraries, both enables and prompts research into techniques that facilitate storage, access, presentation and use of the digitized content. Indeed, the unprecedented scale of the digitization efforts, the unique characteristics of the digitized material as well as the unexplored possibilities of user interactions make full-text book search an exciting area of research.

Motivated by this need, the book search track was launched in 2007 as part of the INEX initiative. INEX was chosen as a suitable forum due to its roots in the evaluation of structured document retrieval (SDR) approaches and since searching for information in a collection of books can be seen as one of the natural application areas of SDR. For example, in focused retrieval a clear benefit to users is to gain direct access to the parts of books (of potentially hundreds of pages) that are relevant to their information need.

The ultimate goal of the INEX book search track (BookSearch'07) is to investigate book-specific relevance ranking strategies, UI issues and user behaviour,

---

<sup>3</sup> <http://www.opencontentalliance.org/>

exploiting special features, such as back of book indexes provided by authors, and linking to associated metadata like catalogue information from libraries. However, searching over large collections of books comes with many new challenges that need to be addressed first. For example, proper infrastructure has to be developed to allow for the scalable storage, indexing and retrieval of the digitized content. In its first year, the track set to explore these issues with the aim to investigate the requirements for such an infrastructure. The track also aimed to run a similar task to the INEX ad-hoc track, where participants could evaluate their relevance ranking strategies.

This paper is organised as follows. Section 2 gives a brief summary of the participating organisations. In Section 3, we briefly describe the retrieval tasks at BookSearch'07. Section 4 details the book corpus, the test topics used as the basis for the track, and relevance assessments. Section 5 lists some obtained evaluation scores. We close with plans for BookSearch'08.

## 2 Participating organisations

In response to the call for participation, issued in April 2007, 27 organisations registered for the track. Of these only a handful of groups remained active during the year. Most groups reported difficulties due to lack of sufficient resources, including space to store the dataset or scalable approach to process it, as well as lack of time or human resources required to tackle the various tasks.

The 27 groups along with details of their participation are summarized in Table 1. As it can be seen, only 10 groups remained active throughout. 16 groups downloaded the book corpus, 7 groups contributed search topics, and only 2 groups managed to submit runs. From the feedback we got from some of the participants, we understand that the size of the corpus presented an issue both in terms of required storage and the necessary scalable indexing and retrieval capabilities. We hope to address some of these concerns in BookSearch'08 by providing smaller collections and less resource intensive tasks (see Section 6).

## 3 Retrieval Tasks

The track defined four tasks: 1) Book Retrieval, 2) Page in Context retrieval, 3) Classification and 4) User intent taxonomy building. A summary of these are given in the following sections. Further details and the various submission DTDs are available in the track's tasks and submission guidelines [5]. At the time of writing, the relevance assessments for the Page in Context task were still outstanding, thus the results for this task are not reported here.

### 3.1 Book Retrieval Task

The goal of this task was to investigate the impact of book specific features on the effectiveness of book search systems, where the unit of retrieval is the

ID	Organisation	Status A/C/P	Corpus download	Topics created	Runs submitted
1	University of Kaiserslautern	C	Y	-	-
2	University of California, Berkeley	A	Y	-	4 BR
4	University of Granada	C	Y	-	-
5	Lexiclone Inc	P	-	-	-
9	Queensland University of Technology	A	Y	-	-
10	University of Otago	C	-	-	-
12	University of Strathclyde	C	-	-	-
14	Wuhan University, China	P	-	-	-
19	Indian Statistical Institute	C	Y	-	-
20	LAMSADE	P	-	-	-
22	Doshisha University	A	Y	1	-
23	Kyungpook National University	A	Y	1	-
25	Max-Planck-Institut für Informatik	P	Y	-	-
26	Dalian University of Technology	A	Y	5	-
28	University of Helsinki	A	Y	2	-
32	RMIT University	P	-	-	-
33	Information Engineering Lab, CSIRO	P	-	-	-
36	University of Amsterdam	A	Y	3	-
37	University of Waterloo	C	Y	-	-
40	Carnegie Mellon University	P	Y	-	-
42	LIP6	P	-	-	-
53	Ecoles des Mines de Saint-Etienne	P	-	-	-
54	Microsoft Research, Cambridge	A	Y	13	-
55	University of Tampere	A	Y	5	-
61	Hong Kong Uni. of Sci. and Tech.	P	-	-	-
68	University of Salford, UK	P	-	-	-
92	Cairo Microsoft Innovation Center	A	Y	-	6 BR, 7 PiC
	Total (27 organisations)	10/6/11	16	30	10 BR, 7 PiC

**Table 1.** Participating groups at BookSearch'07 (In the Status column, A stands for Active, C for Cancelled, and P for Passive; In the Runs column, BR stands for Book Retrieval task, and PiC for Page in Context task)

(complete) book. Users are thus assumed to be searching for (whole) books relevant to their information need which they may want to, e.g., purchase or borrow from a Library.

Participants of this task were invited to submit pairs of runs with the following condition: one of the runs would be the result of applying generic IR techniques to return a ranked list of books to the user, while the other run would extend this technique by exploiting additional book-specific features (e.g. back-of-book index, citation statistics, library catalogue information, etc.) or apply specifically tuned methods. In both cases, a result list could contain a maximum of 1000 books estimated relevant to the given topic, ranked in order of estimated relevance to the query.

Participants could submit up to 3 pairs of runs.

### 3.2 Page in Context Task

This task is equivalent to the ad hoc track's Relevant in Context task, but here it is applied to a collection of digitized books with shallow structural markup. Accordingly, based on the assumption of a focused informational request, the task of a book search system is to return the user a ranked list of books estimated relevant to the user need, and then present within each book, a ranking of relevant non-overlapping XML elements, passages, or book pages. The difference from the Relevant in Context task is that book search systems were required to rank the relevant elements/passages inside the books. The challenge for existing INEX participants was to test the scalability of their XML IR approaches and the adaptability of their search engines to the new domain. This task, however, is, and has proved to be, rather ambitious for most participants. For example, the Wikipedia corpus used in the main INEX ad hoc track experiments totals only about 1GB, whereas the size of the BookSearch'07 collection is 210GB (further details on the collection are provided in Section 4).

Participants were allowed to submit up to 10 runs. One automatic (title-only) and one manual run were compulsory. Additional manual runs were encouraged in order to help the construction of a reliable test collection. Each run could contain for each test topic a maximum of 1000 books estimated relevant to the topic, ordered by decreasing value of relevance. For each book, participants were asked to provide a ranked list of non-overlapping XML elements, passages, or book page results that were estimated relevant to the query, ordered by decreasing value of relevance. A minimum of 1 element/passage/page result per book was required. A submission could only contain one type of result, i.e., only book pages or only passages; alas, result types could not be mixed.

### 3.3 Classification Task

In this task, systems were tested on their ability to assign the correct classification labels from the Library of Congress (LoC) classification scheme to the books of the test corpus based only on information available from the full text of the books. The distributed corpus of about 42,000 books (see Section 4) served

as the training corpus for this task, where classification labels were available for 20,692 books out of the 39,176 that had an associated MARC record. The test corpus contained 2 sets of 1,000 books.

Participants were allowed to submit up to three runs per test set. Each run was required to contain all 1,000 books of the given test set. For each book, systems needed to return a ranked list (or set) of classification labels, with a minimum of one label.

The list of Library of Congress classification headings extracted from the MARC records of the 20,692 books was made available by the organisers on the INEX web site.

### **3.4 User Intent Taxonomy Task**

User intent is a critical component in the understanding of users' search behaviour. It defines what kinds of search tasks users engage in. In traditional information retrieval, a user's intent is assumed to be informational in nature: It is driven by the user's need for information in order to complete a task at hand. Observations of Web use resulted in further two categories: navigational and transactional [1]. It is clear that these can also be applied to the book domain. However, it is possible that there are additional classes of user intent which are specific to books. It may also be the case that user tasks and user behaviour in the book domain will have specific traits and characteristics that may, for example, depend on genre. What are the possible classes of user intent and user tasks and what properties they have is a research question that this task was set to explore.

The goal of this task was to derive a taxonomy of user intent with its associated properties and search tasks. The use of examples of (actual or hypothetical) information needs demonstrating each class of intent and task was encouraged. Such an investigation could extend to include both research and design questions and possible answers regarding how a given user behaviour might be supported by a search system and its user interface. For example, a user hoping to buy a book is likely to be more interested in a price comparison feature, while an informational query will more likely benefit from a "find related books" feature.

Examples of questions that could be explored included: How is user intent dependent on book genre? What book specific features best support the different types of intent and tasks? How could intent be extracted from query logs? How should one design experiments to allow for the identification of user intent from system logs? What data would enable the prediction of intent in order to aid users? What user behaviour follows from them?

Participation in this task involved the submission of a research or opinion paper detailing the proposed taxonomy. Participants could choose to report findings from the analysis of collected user log data or provide recommendations for the design of user studies to help elicit such data.

## 4 Test Collection

### 4.1 Book corpus

The corpus was provided by Microsoft Live Book Search and the Internet Archive (for non-commercial purposes only). It consists of 42,049 digitized out-of-copyright books, and totals around 210Gb in size. The collection contains books from a wide range of genre and includes reference works as well as poetry books. Most of the corpus is made up of history books (mostly American history), biographies, literary studies, religious texts and teachings. There are also encyclopedias, essays, proceedings and novels.

The OCR content of the books is stored in djvu.xml format. 39,176 of the 42,049 books also have associated metadata files (\*.mrc), which contain publication (author, title, etc.) and classification information in MACHine-Readable Cataloging (MARC) record format.

The basic XML structure of a book (djvu.xml) is as follows:

```
<DjVuXML>
<BODY>
  <OBJECT data="file..." [...]>
    <PARAM name="PAGE" value="...">
      [...]
    <REGION>
      <PARAGRAPH>
        <LINE>
          <WORD coords="..."> Moby </WORD>
          <WORD coords="..."> Dick </WORD>
          <WORD coords="..."> Herman </WORD>
          <WORD coords="..."> Melville </WORD>
          [...]
        </LINE>
        [...]
      </PARAGRAPH>
    </REGION>
    [...]
  </OBJECT>
  [...]
</BODY>
</DjVuXML>
```

An <OBJECT> element corresponds to a page in a digitized book. A page counter is embedded in the @value attribute of the <PARAM> element which has the @name="PAGE" attribute. The actual page numbers (as printed inside the book) can be found (not always) in the header or the footer part of a page. Note, however, that headers/footers are not explicitly recognised in the OCR, i.e., the first paragraph on a page could be a header and the last one or more paragraphs could be part of a footer. Depending on the book, headers may include chapter titles and page numbers (although due to OCR error, the page number is not always present).

Inside a page, each paragraph is marked up. It should be noted that an actual paragraph that starts on one page and ends on the next would be marked up as two separate paragraphs within two page elements.

Each paragraph element consists of line elements, within which each word is marked up. Coordinates that correspond to the four points of a rectangle surrounding a word are given as attributes of word elements, and could be used to enable text highlighting.

No additional structure is currently available, although some books have rich logical structure, including chapters, sections, table of contents, bibliography, back-of-book index, and so on.

## 4.2 Topics

The test topics in BookSearch'07 are representations of users' informational needs, i.e, where the user is assumed to search for information on a given subject. For this year, all topics were limited to deal with content only aspects (i.e., no structural conditions). The structure of books, however, could still be used by search engines to improve their ranking of books or book parts estimated relevant to a query.

Two sets of topics were used: 1) a set of 250 queries extracted from the query log of Live Search Books was used for the Book Retrieval task; 2) a set of 30 topics was created by the participating organisations for the Page in Context task. The next sections detail the topic format, the topic creation process for the Page in Context task, and provide a summary of the collected topics.

**Topic Format.** Topics are made up of three parts, each of which describe the same information need, but for different purposes and at different level of detail:

<title>: represents the search query that is to be used by systems. It serves as a short summary of the content of the user's information need.

<description>: is a natural language definition of the information need.

<narrative>: is a detailed explanation of the information need and a description of what makes an element/passage relevant or irrelevant. The narrative must be a clear and precise description of the information need in order to unambiguously determine whether or not a given text fragment in a book fulfills the need. The narrative is taken as the only true and accurate interpretation of the user's needs. Relevance assessments are made on compliance to the narrative alone.

Precise recording of the narrative is also important for scientific repeatability. To aid this, the narrative should explain not only what information is being sought, but also the context and motivation of the information need, i.e., why the information is being sought and what work-task it might help to solve. The narrative thus has the following two parts:

<task>: is a description of the task for which information is sought, specifying the context, background and motivation for the information need.

<infneed>: is a detailed explanation of what information is sought and what is considered relevant or irrelevant.

An example topic is given in Figure 1.

```
<title> Octavius Antony Cleopatra conflict </title>
<description> I am looking for information on the conflict between
    Octavius, Antony and Cleopatra. </description>
<narrative>
  <task> I am writing an essay on the relationship of Antony and Cleopatra
    and currently working on a chapter that explores the conflict between
    Octavius (the brother of Antony's wife, Octavia) and the lovers.
  </task>
  <infneed> Of interest is any information that details what motivated the
    conflict, how it developed and evolved through events such as the
    ceremony known as the Donations of Alexandria, Octavious' propaganda
    campaign in Rome against Antony, Antony's divorce from Octavia, and
    the battle of Actium in 31BC. Any information on the actions and
    emotions of the lovers during this period is relevant. Any
    non-documentary or non-biographical information, such as theatre plays
    (e.g., Shakespeare's play) or their critics are not relevant.
  </infneed>
</narrative>
```

Fig. 1. Example topic (not part of the BookSearch'07 test set).


### 4.3 Topic Creation and Collected Topics

**Topics for the Book Retrieval Task.** 250 queries were extracted from the query logs of Live Search Books for which the test corpus contained a minimum of one relevant book. No additional background or context information was available for these queries. Therefore these topics only have topic titles; and both the description and the narrative fields are left empty. These queries were used as test topics in the Book Retrieval Task, where systems aimed to retrieve (whole) books relevant to the user request.

On average, a query contained 2.188 words, the longest query being 6 words long. The distribution of queries by length is shown in Figure 2.

**Topics for the Page in Context Task.** Participants were asked to submit candidate topics for which at least 3 but no more than 20 relevant books were found during the collection exploration stage [6]. Participants were provided with a collection exploration tool to assist them in their topic creation. A screenshot of the tool is given in Figure 3.





**Fig. 2.** Distribution of queries by length (in number of words).

This tool gave participants the means to search and explore the book corpus. This was achieved by building an interface to the search service provided by Live Search Books<sup>4</sup>. The tool took advantage of the fact that all books in the BookSearch'07 collection are indexed by Live Search Books. It worked by first sending the query entered by the user to the the Live Search Books search engine, and filtering the result list so that only books of the BookSearch'07 corpus were shown. Clicking on any of the books in the ranked list, took the user directly to the book viewer of Live Search Books (see Figure 3). Using this tool, participants could familiarize themselves with the collection and determine whether a candidate topic met the necessary criteria to be considered as a test topic: creation of topics with too few or too many relevant answers had to be aborted as these are not suitable for testing system performance [6]).


A total of 30 topics were created, complete with topic title, description and narrative (as described in Section 4.2). Table 1 shows the number of topics each participating group contributed.

Participants were allowed to create topics based around the queries used for the Book Retrieval task. A query thus served as a starting point for participants to build up an information need during the collection exploration phase. Based on the similarity between the topic title of the created topic and the original query, we can distinguish the following categories: full, partial and no match. 10 topics belong in the full match category, meaning that the created topic title is exactly the same as the original query. 9 topics have partial matches, where participants refined the focus of the query, usually narrowing the scope. The remaining 11 topics were created from scratch.

#### 4.4 Relevance Assessments

**Relevance Assessments for the Book Retrieval Task.** The relevance assessments for the 250 queries used for this task were collected by Live Search Books from human judges. Judges were presented with a query and a set of books

<sup>4</sup> <http://books.live.com>, or <http://search.live.com/results.aspx?mkt=en-US&scope=books&FORM=BBRE>



**Fig. 3.** Screenshot of the system used to assist topic creation at BookSearch'07. The window on the left shows the main search window of the system. It allowed participants to enter a query and view the ranked list of books. The screen on the right is the book viewer window of the Live Search Books service, which allowed participants to explore the contents of a book for relevant information.

to judge. Assessment were made along a four point scale: Excellent, Good, Fair, and Non-relevant.

In total, 3,918 relevant books are contained in the assessment set. These include 1061 Excellent, 1,655 Good, and 1,202 Fair judgments. The average number of relevant books per query is 15.672, with a maximum of 41. The distribution of number of relevant books per topic is shown in Figure 4.

**Relevance Assessments for the Page in Context Task.** Relevance judgments for the Page in Context task are to be provided by the participants of the track. At the time of writing, the relevance assessment system was still being finalised and thus the collection of judgments has not yet started. The assessment system was implemented by adapting XRai [7] and integrating it with the book viewer of Live Search Books. Figure 5 shows a screenshot of the assessment system.

## 5 Submissions and Evaluation Results

As shown in Table 1, only two groups submitted retrieval runs to the Book Retrieval task and only one group to the Page in Context task. The University




Fig. 4. Distribution of relevant books per query.




Fig. 5. Screenshot of the Page in Context assessment system. The main frame shows the current book to be assessed, using the Live Search Books service. The frame on the left-hand side of the browser shows the list of pages to be assessed (belonging to the assessment pool). If a page number is clicked on, the corresponding page will display on the main frame. For each book in the pool, the assessor is expected to mark all the relevant pages and submit her assessments. To ease this process, fast selection is provided through “select all”, “select none”, and “text-in” functionalities. While the first two are self-explanatory, the latter offers a simple syntax to select a number of pages with limited effort. For instance, the input “18-36; 49” will cause the automatic selection of all the pages between 18 and 36 (inclusive), as well as page 49.

of California, Berkeley has also participated in the Classification task, but only evaluated its results unofficially. No submissions were received for the User Intent Taxonomy task. This was a bit of a surprise as we designed the task with the aim to open up the track and allow participation without the requirement of a working book search engine.

To evaluate runs submitted to the Book Retrieval task, we employed the measure of Normalized Discounted Cumulated Gain [4], using the discount function of  $1/\log_b(i)$ , where  $b = 2$ , and where the discounted cumulated gain for a given ranking is calculated as:

$$DCG[i] = \begin{cases} \sum_i G[i] & \text{if } i \leq b, \\ DCG[i-1] + \frac{G[i]}{\log_b(i)} & \text{if } i > b. \end{cases} \quad (1)$$

The normalized DCG scores are obtained by dividing the DCG vector of the system’s ranking by the DCG vector of the ideal ranking. The gain associated with a relevant book was 3 for a book rated Excellent, 2 for a book judged Good, and 1 for a Fairly relevant book. Irrelevant and unjudged books gave 0 gain.

Table 2 shows the NDCG scores, reported at various rank cutoffs. From the University of California, Berkeley results, it appears that performance at top ranks (up to rank 25) is improved using book-specific features or ranking. However, the results of Cairo Microsoft Innovation Center show that superior performance is achieved by simply applying traditional document retrieval techniques. For details on the approaches of the two groups, please refer to [8] and [9].

Overall, we can observe a large variation in the performance scores, from 0.206 to 0.613, which suggests that there is plenty of room for further development.

ID	RunID	Query	Method	NDCG	NDCG	NDCG	NDCG	NDCG	NDCG
		A/M	N/B	@1	@5	@10	@25	@100	@1000
2	BERK_T2.OBJ **	A	N	0.351	0.316	0.316	0.349	0.427	0.478
2	BERK_T2.OBJ2 *	A	N	0.351	0.316	0.316	0.349	0.427	0.478
2	BERK_MARC_T2FB **	A	B	0.446	0.349	0.334	0.343	0.394	0.439
2	BERK_T2_CC_MARC *	A	B	0.453	0.375	0.359	0.371	0.422	0.462
92	Indri-F-C-A	A	N	0.521	0.477	0.479	0.503	0.562	0.604
92	Indri-NF-C-A	A	N	0.527	0.490	0.490	0.514	0.573	0.613
92	Indri-NF-PC-A	A	N	0.319	0.319	0.331	0.359	0.425	0.488
92	Indri-F-TOC-A	A	B	0.241	0.218	0.206	0.219	0.262	0.305
92	Indri-NF-TOC-A	A	B	0.257	0.233	0.225	0.235	0.275	0.316
92	Indri-NF-H-A	A	B	0.511	0.421	0.398	0.399	0.440	0.478

**Table 2.** Performance scores for the Book Retrieval task (In the Query column, A stands for Automatic, and M is for Manual; in the Method column, N stands for Non-book-specific retrieval approach, and B for Book-specific approach). Paired runs are indicated by \* (where the information was available).

## 6 Plans for BookSearch'08

The Book Search track in 2007 focused on investigating infrastructure issues that come with the setting up of a new track. A range of tasks were defined: some of them extending established focused retrieval tasks studied at INEX to the book domain and some novel, more book-specific tasks. The tasks were designed with the aim to provide new challenges for participants with existing search engines, as well as to attract new groups with an interest in digitized books. Although most of these tasks proved to be rather ambitious, they represent a significant step in the shaping of a research agenda for the future of book search. The level of interest (27 registered groups) suggests that book search is an area that is set to grow considerably in the coming years, especially as more and more groups will be able to muster the necessary resources to tackle the range of challenges.

The Book Search track in 2008 (BookSearch'08)<sup>5</sup> will aim to look beyond the topic of search and extend to issues that touch a wider research community. BookSearch'08 will aim to bring together researchers in Information Retrieval, Digital Libraries, Human Computer Interaction, and eBooks with the goal to work on a common research agenda around digitized book collections. Towards this goal, the track will investigate the following topics:

- Users' interactions with e-books and collections of digitized books
- IR techniques for searching full texts of digitized books
- Digital library services to increase accessibility of digitized books

We plan to propose five tasks for 2008 and invite participants in the setting up process. The tasks are 1) Structure extraction from digitized books, 2) Creation of virtual bookshelves, 3) Supporting active reading, and the 4) Book retrieval, and 5) Page in Context tasks from BookSearch'07. The different tasks will make use of different sets of digitized books, ranging from a collection of 100 books to 50,000.

The track is set to start in mid April 2008.

## Acknowledgements

We thank Steven Robertson, Nick Craswell and Natasa Milic-Frayling for their valuable comments on aspects of the organisation of this track.

## References

1. Andrei Broder. A taxonomy of web search. *SIGIR Forum*, 36(2):3–10, 2002.
2. K. Coyle. Mass digitization of books. *Journal of Academic Librarianship*, 32(6):641–645, 2006.

---

<sup>5</sup> <http://www.inex.otago.ac.nz/tracks/books/books.asp>

3. Norbert Fuhr, Jaap Kamps, Mounia Lalmas, and Andrew Trotman, editors. *Focused access to XML documents, Sixth International Workshop of the Initiative for the Evaluation of XML Retrieval, Revised Selected Papers*, Lecture Notes in Computer Science. Springer, 2008.
4. Kalervo Järvelin and Jaana Kekäläinen. Cumulated gain-based evaluation of IR techniques. *ACM Transactions on Information Systems (ACM TOIS)*, 20(4):422–446, 2002.
5. Gabriella Kazai. INEX 2007 book search track, tasks and submission guidelines. In Fuhr et al. [3].
6. Gabriella Kazai. INEX 2007 book search track, topic development guidelines. In Fuhr et al. [3].
7. Mounia Lalmas and Benjamin Piwowarski. INEX 2007 relevance assessment guide. In Fuhr et al. [3].
8. R. R. Larson. Logistic regression and evis for xml books and the heterogeneous track. In Fuhr et al. [3].
9. W. Magdy and K. Darwish. Cmic at inex 2007: Book search track. In Fuhr et al. [3].