Lecture 11
Practical Examples with Specific Problems

Memory Queue
Priorities
Disk Sub-System
CPU Scheduling
Paging

 Copyright Teemu Kerola 2002

Problems

- Memory queue — Simultaneous resource possession
- Disk subsystem — Complex sub-model
- CPU scheduling — Priorities
- Paging — Dependence on other jobs

- General: non-product form

 Copyright Teemu Kerola 2002

Non-Product Form Solutions

- Use your imagination and know-how
- Flow equivalence
- Load concealment
- Change model
- Multi-level modeling
- Simulation
- Hybrid simulation

 Copyright Teemu Kerola 2002

Flow Equivalent Server

- Fig. 8.2
- Approach OK, if sub-model is "busy" part of model
  - many state transitions within sub-model as compared to transitions between sub-model and rest of the original model
- Hierarchical models
  - orig model, sub-model, aggregate model

 Copyright Teemu Kerola 2002

Modeling Memory

- Fig. 8.1
- Original model not product form
- Use FESC, max mpl 5
  - short cut sub-system to closed model
  - solve for all mpl={1,2,3,4,5}
  - create service times for FESC: $S^{FESC}(k) = 1/X^{SUBSYS}(k)$
  - solve new model (or models), Fig. 8.3
    - solve open class first, slow down FESC
    - solve closed class

Memory Constraint, One Class



Not product form! Why? Simultaneous resource possession

source:[Men 94, p. 239]

One Class Example



- Isolate system, use shortcuts
- Solve pprduct form model for mpl={1,2,3}
  - use MVA: X= {1, 1.413, 1.623}
- Create FESC: S(n) = {1, 1/1.413, 1/1.623, 1/1.623, ...)
  = {1, 0.708, 0.616, 0.616, …}
- Create new model
  - birth-death process
  - state dependent serv. rate: X= {1, 1.413, 1.623}



Solve Birth-Death Model (5)



$P_0 = 0.260$, $P_1 = 0.260$, $P_2 = 0.184$, $P_3 = 0.113$,
$P_{N>3} = 1 - 0.260 - 0.260 - 0.184 - 0.113 = 0.183$

average jobs in mem $= 0 * P_0 + 1\ P_1 + 2\ P_2 + 3\ (P_3 + P_{N>3})$
$= 0.260 + 2 * 0.184 + 3 * 0.296 = 1.516$

average number of waiting for memory jobs: $N_w = \sum_{i=1}^{\infty} iP_{i+3} = \frac{P_0 \lambda^3}{\mu_1 \mu_2 \mu_3} \frac{\lambda / \mu_3}{[1-(\lambda / \mu_3)]^2} = 0.474$

total popul = 1.516 + 0.474 = 1.99

time spent in memory queue: 0.474/1.99 = 23.8%

Memory Constraint, Many Classes

- Each class c has its own constraints J_c
  - each class in its own domain
  - classes are independent

4 segm for class 1
1 segm for class 2



 Copyright Teemu Kerola 2002

Multiple Domain Solution

- Assumptions
  - Class r population is independent of population in other classes
  - Throughput in class r depends only on *average* populations in other classes:

$$X_r(n_r) = f(\bar{n}_1, \bar{n}_2, \ldots, n_r, \ldots, \bar{n}_R)$$

- Iterative solution, one class at a time
  - solution for each class is not quite simple...

 Copyright Teemu Kerola 2002

Model with Memory, Multiple Classes Iterative Solution

- Guess initial average populations $\overline{N}$
- Solve one class *r* at a time for population $\overline{N} = (\overline{n}_1, \overline{n}_2, \ldots, n_r, \ldots, \overline{n}_R)$
  - Get new average population for each class r: $\overline{n}_r, X_r, R_r, U_{kr}$

$$\overline{N} = (\overline{n}_1, \overline{n}_2, \ldots, \overline{n}_r, \ldots, \overline{n}_R)$$

- Iterate until "convergence"

$$\overline{N} = (2.1, 5.3, 2)$$

Iterative Memory Solution

- 1. Initialize
  - solve network without memory queue
  - get average popul. for each class: $\overline{n}_r^{nomem}$
  - set initial $\overline{n}_r = \min(\overline{n}_r^{nomem}, J_r)$
- 2. Create transformed model
  - remove memory constraint
  - make all memory constrained classes c closed (batch) job classes

Iterative Memory Solution (contd)

- 3. Solve the model for all constrained classes c, one class at a time:
  - solve it for populations



    Approx MVA... why?

    population not integers!

    - get $X_c(n_c)$ for this class $\forall\ n_c \in \{1,\ldots,J_c\}$
  - create <u>single class</u> memory queue birth-death model for class c, with system as FESC
    - solve it, get new $\bar{n}_c$ = "average number of jobs in memory"
  - iterate until "done"

Iterative Memory Solution (contd)

- 4. Iterate step 3 until convergence
- 5. Get performance results for constrained classes c from the latest solutions for each such class
- 6. Solve model for unconstrained classes, using fixed $\bar{n}_c$'s constrained classes

Multiple Class Example



- Two class model, Tbl 8.1
- Step 1. Solve open model without memory constraint

$\bar{n}^{nomem} = (6.0192, 0.8540)$ → max pop = max mpl

init $\bar{n} = (\bar{n}_Q, \bar{n}_U) = (4.0, 0.8540)$

Multiple Class Example (contd)

- Steps 2 & 3.

Single class open model

$\lambda_Q = 4.2$

$$\bar{n} = (1.0, 0.8540) \overset{appr.MVA}{\rightarrow} X_Q(1) = 2.542$$
$$\bar{n} = (2.0, 0.8540) \overset{appr.MVA}{\rightarrow} X_Q(2) = 3.577$$
$$\bar{n} = (3.0, 0.8540) \overset{appr.MVA}{\rightarrow} X_Q(3) = 4.115$$
$$\bar{n} = (4.0, 0.8540) \overset{appr.MVA}{\rightarrow} X_Q(4) = 4.434$$

$$S = \left(\frac{1}{2.542}, \frac{1}{3.577}, \frac{1}{4.115}, \frac{1}{4.434}, \frac{1}{4.434}, \ldots \right)$$

Birth-death

$\bar{n}_Q = 3.648$

Steps 4 & 5 Tbl 8.2 Tbl 8.3

Priorities with Shadow Server



- Two job classes: Tbl 8.6
- No priorities: R = (2.69, 8.19) appr. MVA
  (2.37, 6.74) from PMVA

PMVA listing fig.8.6a.out

Shadow Server



- Class P: CPU "just for it"
- Class D: sees a "shadow" CPU as slower device
  - how much slower? $1/(1-U_{CPU,P}) = 1/(1-0.291)$
  - inflate demands D_{kD} this much for class D
- Get: model with no priorities

PMVA listing fig.8.6b.out

Fig 8.6 [Men 94]

PMVA listing fig.8.6.out

15.4.2002 Copyright Teemu Kerola 2002 21

Many Priority Levels

- Generalized solution method for many priority levels
- Each level (but the one with highest priority) will get their own shadow server

Alg. 11.1 [LZGS 84]

- Shadow server utilizations of no use

15.4.2002 Copyright Teemu Kerola 2002 22

Another Simple Example

(from Distr. OS homework)

- We consider a supermarket with one check-out ("kassa"). A client arrives once every 3 minutes, and the average service time is 2.5 minutes. During a day, how long is the check-out clerk idle? On the other hand, how long will a client spend in the queue?
- Every fifth client has only one purchase, and for him/her the service time is only half a minute. The manager wants to improve the service for these "express clients". Two alternatives are considered: 1) an "express client" may pass the queue (but he/she is or she is not allowed to interrupt an ongoing service), 2) a new check-out is established for the "express clients".
- How would these alternatives affect the performance of the check-out service? Which alternative is better?
- How would it be possible to guarantee "express service" for "express clients" that the total delay is less than one minute?

15.4.2002 Copyright Teemu Kerola 2002 23

Another Simple Example (contd)

- Basic 1-class solution — slides ASE 1-3
- Priority pre-emptive solution — slide ASE 4
- Priority non pre-emptive solution — slides ASE 5-7
- 2-server solution — slide ASE 8
- Basic 2-class solution — slides ASE 9-13

15.4.2002 Copyright Teemu Kerola 2002 24

Paging



- Page fault rate depends on behaviour of other jobs, and total number of jobs in system
- Is paging disk the same unit as for files?

$D = D^{paging} + D^{file}$

nr of page faults * S^{paging}

Paging (contd)

- Nr of page faults?
  - Fig 8.8
  - Fig. 9.5 from [LZGS 84]
  - Nr page faults:

$$\frac{D_{cpu}}{IFT(f)} = \frac{D_{cpu}}{IFT(\frac{NP}{n})} = \frac{6 \text{ sec}}{1.5 \text{ sec / fault}} = 4 \text{ faults}$$

total Nr of Pages

nr of frames in average

Paging (contd)

$$D_{disk}^{paging} = \frac{D_{cpu}}{IFT(f)} \; S_{disk}^{paging} = \frac{D_{cpu}}{D_{cpu} \Big/ \left(1 + \left(\frac{a}{NP/n}\right)^2 - \left(\frac{a}{F}\right)^2\right)} S_{disk}^{paging}$$

$$= \left[1 + \left(\frac{a}{NP/n}\right)^2 - \left(\frac{a}{F}\right)^2\right] S_{disk}^{paging}$$

F = nr of frames in virtual addr space

$$D_{disk} = \begin{cases} D_{disk}^{file} + D_{disk}^{paging} & \text{if } nF > NP \\ D_{disk}^{file} & \text{o / w} \end{cases}$$

Paging Example



page frame size

paging mem

- Memory NP=10M/1K =10K = 10240
- Virt. addr. space = 2 MB
  - nr virt pages F = 2MB/1K = 1K = 2048
- match IFT(f) to data: magic a=4000

$$D_{d2}(n) = D_{d2}^{paging}(n) = \left[1 + \left(\frac{4000}{10240/n}\right)^2 - \left(\frac{4000}{2048}\right)^2\right] * 0.03$$

$$= \left[1 + 0.153n^2 - 3.81\right] * 0.03 \quad \text{if } n > \frac{NP}{F} = \frac{10240}{2048} = 5$$

$$D_{d2}(n) = 0 \qquad \text{o / w (i.e., } n \le 5\text{)}$$

 Copyright Teemu Kerola 2002

Paging Example (contd)



- Modify MVA to account for varying demand
- Solve, get system throughput as fn of load
  - Fig. 8.9
- X, R, U as function of load:
  - Figs. 9.6-9.8 from [LZGS 84]

 Copyright Teemu Kerola 2002