Komponenttiväliohjelmistot

CORBA Component Model (CCM) jatkoa… korjatulla esitysjärjestyksellä

CORBA-komponenttimalli CCM

- abstrakti komponenttimalli
- komponenttien suoritusaikainen ympäristö
  - Component container programming model
- komponenttien toteutus
  - Component Implementation Framework CIF + Component implementation language CIDL
- Komponenttien pakkaaminen ja käyttöönsaatto

A CORBA Component



Component runtime support

- Component home
  - Controls a set of components using the component equivalent interface
  - Provides component factory facilities
    - Specializations
- Container
  - Defines the environment for supporting dynamic collections of components
  - The core of the CCM is the container: a running piece of code that you buy from a vendor and install on your server machine. The container includes an ORB with a POA. Corba components are server-side objects; your system administrator installs components into the container, which takes charge of them when they run.

A CORBA Component Home



Component Home

- Is instantiated at deployment time
- Manages a unique component type
  - More than one home type can manage the same component type
  - But a component instance is managed by a single home instance
- Allows life cycle characteristics or key type to vary/evolve without changing component definition
- Optional use of `primarykey` for business component identity and persistency primary key
- Standard `factory` and `finder` business logic operations
- Extensible with arbitrary user-defined business logic operations

Primary Keys

- Values exposed to clients to create, find, and destroy component instances
  - Uniquely identifies a component instance within a home
  - Assigned at creation time, or in pre-existing database
  - Must be a value type derived from Components::PrimaryKeyBase (empty, abstract)
- Association between a primary key and a component is defined and maintained by its home
  - Different home types may define different key types (or no key) for the same component type
  - Primary key is not necessarily a part of the component's state

Komponenttien suoritusaikainen ympstö

- component container model
  - Framework for component application servers
  - Mostly built on the POAs
    - Automatic activation/deactivation
    - Resource usage optimization
    - Provides simplified interfaces for corba services
    - Uses callbacks for instance management
  - Container encapsulates 1-N POAs
  - References exported thourhg component home finder, naming or trading

The Container Architecture



CCM Container model

- CORBA Usage Model
  - Describes the interaction between the container, the POA and the CORBA services, ie reference persistence and servant to ObjectID mapping
  - Types: stateless, conversational, durable
- Component categories
  - Combination of internal and external APIs

usage model	container API	comp.category	object ref	servant/OID
stateless	session	service	transient	1:N
conversational	session	session	transient	1:1
durable	entity	process	persistent	1:1
durable	entity	entity	persistent	1:1

CCM Container model

- Components define their runtime requirements through (in the deployment descriptor)
  - Usage model
  - Component category
  - Activation and servant lifetime management
  - Transaction policies
  - Security policies
  - Events
  - Persistence
  - Compoent level (basic-ejb-compat, extended)

CCM container model

- component activation and servant lifetime management
  - Each container has a POA and servantLocator
  - Policies
    - Method: activate/passivate by method-basis
    - Transaction: lifetime tied to a transaction
    - Component: component decides itsef on deactivation
    - Container: lifetime tied to container's lifetime
  - Depends also on component category

characteristics	property (service)
internal interface	session context (basic) or Session2Context (extended)
callback interface	session component
usage model	stateless
extenral API type	keyless
client design pattern	factory
servat lifetime mgmt	method (only)

characteristics	property (entity)
internal interface	entitycontext(basic) or entity2context(extended)
callback interface	EntityComponent
usage model	durable
extenral API type	keyfull
client design pattern	factory or finder
servat lifetime mgmt	any

The Container Server Architecture



CCM (xx) - Container Model

- Invocation example (Service comp.)



CCM (xxi) - Container Model

- Invocation example (cont'ed)



- The same for Session components, but...
  - Repeat (5) - (8) as needed

Cmponent Implementation Framework

- CIF defines a programming model for constructing component implementations
  - How components should be implemented
  - Generates executors: implementation of behavioural elements (homes, containers, ...)
- Facilitates component implementation
  - "only" business logic should be implemented
    - Not activation, identify, port management and introspection
  - -> Local server-side OMG IDL mapping
    - Interactions between implementations and containers
- Manages segmentation and persistency
  - -> Component Implementation Definition Language

Component Implementation Framework to Component Skeleton Generation



A Monolithic Component Executor



CIF

- implementations can be segmented
  - Segments are physical partitions of implementations
  - Can define independent state and can be independently activated
  - Help in managing, partitioning and sharing a high number of facet implementations
  - Only in process and entity categories

A Segmented Component Executor



Building CCM Applications = Assembling CORBA Component Instances



CCM development project stages

1. Analysis/design
   - UML + business object profiles
2. Component declaration
   - Define component's methods and home with extended IDL and compile to produce
     - for clients: Operations, navigation operations, stubs
     - for servers: skeletons, IR entries, some code, packaging and deployment descriptors in XML

Esimerkki

```
component ShoppingCart {
    provides ShoppingCartIntf Cart1;
    uses CheckoutIntf CheckOut1;
}
home ShoppingCartHome manages
  ShoppingCart{};
```

CCM development project stages

3. component implementation
   - declare component's persisent state in PSDL and some behaviour aspects in CIDL
   - compile to get skeletons; fill in with business logic; compile to joint result to get compiled libraries

Esimerkki

```
abstract storagetype CustomerState{
   state long AcctNum;
   state ...
}
storagetype PortableCustomerState implements CustomerState{};
typedef sequence <Customer> CustomerList;
abstract storagehome CustomerStorageHome of Customer {
      primary key AcctNum(AcctNum);
      factory create(AcctNum, Name, ...);
}
storagehome PortableCustomerStorageHome implements
   CustomerStateHome{};
```

Relations between OMG Definition Languages

- OMG IDL 2.x
  - Object-oriented collaboration
  - i.e. data types, interfaces, and value types
- OMG IDL 3.0
  - Component-oriented collaboration
  - i.e. component types, homes, and event types
- OMG PSDL
  - Persistent state definition
  - i.e. [abstract] storage types and homes
- OMG CIDL
  - Component implementation description
  - i.e. compositions and segments



Component Implementation Definition Language CIDL

- describes component composition
  - Aggregate artifacts required to implement a component and its home
- Manages component persistent state
  - Persistent state definition language PSDL
  - Links storage types to segmented executors
- Generates executor skeletons providing
  - Segmentation of component executors
  - Default implementations of callback operations
  - Component's state persistency



Composition

Defined in CIDL
- Category
- Home executor
- Executor
- Bindings
- State management (storage)

- 7 component categories: 4 CCM, 2 EJB, 1 clustomizable
- servant lifetime policies: method, transaction, component, container

category

usage	container model	primary API type	key
service	stateless	session	no
session	conversational	session	no
process	durable	entity	no
entity	durable	entity	yes

Esimerkki

```
composition entity CustomerImpl {
    implements Customer;
    home executor CustomerHomeImpl
      delegatesTo abstractstoragehome
      CustomerStateStorageHome;
}
```

CCM development project stages

4. component packaging
   - (use interactive tools to produce)/write component descriptor (in XML) to tell CCM runtime how to connect up and manage the implementation
   - package up implementation and component descriptor into a component archive file CAR

5. component assembly
   - An application or part composed of some components with predefined interaction pathways in an assembly archive file AAR
   - Customizes configuration, connections, partitioning to different computers

CCM development project stages

6. component deployment and installation
   - Prior to this: system admin has installed and configured runtime environement
     - Installer program for CARs
   - Deploy component factories and managers
7. Runtime: component instance activation
   - Part of the application logic
   - Components are activated by the container POA

Esimerkki

```
<componentassembly id="374...2304">
<description>Assembly descr for example
</description>
<componentfiles>
<componentfile id="ShoppingChartFIle">
<fileinarchive name="shoppingchar.car">
</componentfiles>
<partitioning>
<homeplacement id ="ShoppingCartHome">
<componentfileref idref="ShoppingCartFIle">
</homeplacement>
...
</partitioning>
<connections>
<connectinterface>
<usesport>
<usesidentifier>Check1</usesidentifier>
<homeplacementref idref="ShoppingChartHome">
...
```

The Client Programming Model

- Component-aware and -unaware clients
- Clients see two design patterns
  - Factory – Client finds a home and uses it to create a new component instance
  - Finder - Client searches an existing component instance through Name Service, Trader Service, or home finder operations
- Optionally demarcation of transactions
- Could establish initial security credentials
- Invokes operations on component instances
  - Those defined by the client-side mapping

Packaging and Deployment

- Packaging and Deployment of Components
  - Components are packaged into a self-descriptive package
  - Packages can be assembled
  - Assemblies can be deployed
- Helped by XML descriptors
- Packaging and Deployment model Allows interoperability between deployment tools and containers

CCM Applications Deployment

- It is necessary for an application to
  - List component instances
  - Define logical location and partitioning
  - Specify connections between components
- It is necessary for a component to
  - Specify its elements
    - interfaces, implementations
  - Describe system requirements
    - OS, ORB, JVM, library releases, ...
  - Specify its initial configuration
- It is necessary for a connection to
  - Associate related component ports

Component Packaging Artifacts



XML Descriptors Overview

- Software Package Descriptor (.csd)
  - Describes contents of a component software package
  - Lists one or more implementation(s)
- CORBA Component Descriptor (.ccd)
  - Technical information mainly generated from CIDL
  - Some container managed policies filled by user
- Component Assembly Descriptor (.cad)
  - Describes initial virtual configuration
    - homes, component instances, and connections
- Component Property File Descriptor (.cpf)
  - name/value pairs to configure attributes

Relationship Between CCM XML Descriptors



Component Assembly Package

- Archive (ZIP file) containing
  - One or more component packages, either
    - Including a package's contents
    - Including the original package
    - Referencing the package by URL
  - Property File Descriptors defining initial attribute values
  - Component Assembly Descriptor (.cad)
    - Defines home instances to be created
    - Defines component instances to be created
    - Defines connections between ports to be made
- Self-contained and self-descriptive unit
- For automatic and easy "one step" deployment
- No programming language experience necessary

Component Assembly Descriptor (.cad)

- References one or more Component Software Descriptors
- Defines home instances and their collocation and cardinality constraints
- Defines components to be instantiated
- Defines that homes, components or ports are to be registered in the ComponentHomeFinder, Naming or Trading Service
- Defines connections to be made between component ports, e.g. receptacles to facets and event sinks to event sources

Software Package Descriptor (.csd)

- Descriptive general elements
  - title, description, author, company, webpage, license
- Link to OMG IDL file
- Link to default property file
- Implementation(s)
  - Information about Implementation
    - Operating System, processor, language, compiler, ORB
    - Dependencies on other libraries and deployment requirements
    - Customized property and CORBA component descriptor
  - Link to implementation file
    - Shared library, Java class, executable
  - Entry point

CORBA Component Descriptor (.ccd)

- Structural information generated by CIDL
  - Component / home types and features
  - Ports and supported interfaces
  - Component category and segments
- Container policies filled by the packager
  - Threading
  - Servant lifetime
  - Transactions
  - Security
  - Events
  - Persistence
  - Extended POA policies
- Link to component and home property files

Property File Descriptor (.cpf)

- Used to set home and component properties
  - However, it could be used for anything
- Contains zero or more name/value pairs to configure attributes
- Referenced by…
  - Software Package Descriptors to define default values for component attributes
  - CORBA Component Descriptors to define default values for component or home attributes
  - Assembly Descriptors to configure initial values for home or component instances

Component Packaging



Component Assembly



Deployment

- An Assembly Archive is deployed by a deployment tool
- The deployment tool might interact with the user to assign homes and components to hosts and processes
- The deployment application interacts with installation objects on each host

Deployment Objects

- `ComponentInstallation`
  - Singleton, installs component implementations
- `AssemblyFactory`
  - Singleton, creates `Assembly` objects
- `Assembly`
  - Represents an assembly instantiation
  - Coordinates the creation and destruction of component assemblies and components
- `ServerActivator`
  - Singleton by host, creates `ComponentServer` objects
- `ComponentServer`
  - Creates `Container` objects
- `Container`
  - Installs `CCMHome` objects

The Component Deployment Process



The Component Deployment Process



More Information

- CORBA 3.0: New Components Chapters
  - OMG TC Document ptc/2001-11-03
- CORBA 3 Fundamentals and Programming
  - Dr. John Siegel, published at John Wiley and Sons
- "The CCM Page", Diego Sevilla Ruiz
  - *http://www.ditec.um.es/~dsevilla/ccm/*

Kurssilukemisto

- Vinoski, S., New features for CORBA 3.
- Wang, Schmidt, O'Ryan: Overview of the CORBA Component Model

Muuta materiaalia

- CCM-spesifikaation intro
  - http://www.omg.org/cgi-bin/doc?formal/02-06-69
- Ohjelmointitutoriaaleja
  - http://www.cs.wustl.edu/~schmidt/ACE_wrappers/TAO/docs/tutorials/Quoter/
  - useimmilla toimittajilla omansa (Sun+Java+CORBA, etc)
- CORBA-sivustoja
  - http://www.cs.wustl.edu/~schmidt/corba.html
  - http://www.puder.org/corba/

Open Source CCM Implementations

- OpenCCM from LIFL & ObjectWeb
  - Java on ORBacus 4.1 & OpenORB 1.2.1
  - http://www.objectweb.org/OpenCCM/
- MicoCCM from FPX & Alcatel
  - C++ on MICO
  - http://www.fpx.de/MicoCCM/
- FreeCCM from Humboldt University
  - C++ on ORBacus 4.1
  - http://sourceforge.net/projects/cif

Commercial CCM Implementations

- EnagoCCM from IKV++/Fraunhofer FOKUS
  - C++ on MICO & ORBacus 4.1
  - ritter@fokus.gmd.de
- EJCCM from CPI Inc.
  - Java on OpenORB 1.3.x
  - http://www.ejccm.org
- K2 from ICMP
  - C++ on various ORBs
  - http://www.icmgworld.com

Komponenttimallien vertailua

Java component models

- applets – client side, downloadable lightweight component for augmenting websites display
- JavaBeans – focuses on supporting connection-oriented programming, for clients and servers
- Enterprise Java Beans, EJB – container-integrated services supporting components that request services using declarative attributes and deployment descriptors
- servlets – lightweight componetns instantiated by web server processing web pages
- application client components – uncontstrained Java application

EJB Overview

- EJB Architecture contracts
  - Client view contract between client and container
    - Client can be servlet or JSP, standalone Java application, applet, another EJB (same/different container), web services client
    - Provides development model for clients
  - Component contract between EJB component and its container
    - Runtime environment, development model

EJB Overview

- Client view contract is comprised of
  - Home interface
    - Methods for creating and locating beans
  - Remote interface
    - Business methods for clients
  - Object identity
  - Metadata interface
  - handle

EJB Overview

- component contract
  - Enables EJB method invocations from clients
  - Manages the life cycle of EJB bean instances
  - Implements home and remote interfaces
  - Provides persistence
  - Provides runtime context information
  - Manages transactions, security, exceptions, ...
  - Implements callbacks

EJB Overview

- Deployment process defined
  - Deployment descriptor includes instructions for container on how to control transactions, security, lifecycle, state management, persistence, ...
  - Describes structural and external dependencies of enterprise bean

Component model comparison

- both CCM and EJB provide
  - component model with stateless and statefull sessions and entities
  - services for building scalable applications (load-balancing etc)
  - access to components via HTTP or distributed object protocol
  - Transaction support
  - Development tools

Component model comparison

- EJB interoperability is explicitly defined in the CCM specification
- CCM defines both "container to component" and "container to infrastructure contract"
- CCM's container environment specification is a superset of EJB 1.1 containter environment specification

CCM Container Architecture



EJB Container Architecture



Component model comparison

- CCM
  - lookup and instantiation of objects on remote hosts
  - marchalling
  - security across mach. bound.
  - IIOP and GIOP
  - Objects handled via object reference
  - Error handling via exceptions
  - Multiple interfaces
  - Necessary services (in CACM):
    - Naming, transactions, events
- EJB
  - invocation of object methods, serialization
  - JRMP/IIOP
  - Server-side beans that process business logic,
  - Single interfaces only
  - Supports transactions
  - RMI – easy to use
  - Not language-independent
  - Better third-party market

Component container environments

- CCM container managed policies
  - Servant lifetime
  - Transaction: flat, operation level
  - Security
  - Notification/events
  - persistence
- EJB container manages
  - Component lifecycle, resource pooling, load balancing
- EJB component descriptor
  - Persistence
  - Transaction
  - security

Usability comparison

- why multi-tier architecture?
- flexibility
  - middle-tier business services accessible by many different types of clients
- scalability
  - Optimization of resource sharing in middle-tier
- Robustness
  - Interchangeable servers deliver business services

- A comparison framework