

Distributed Systems Project, Spring 2015, First exercise

Select this assignment if (your student ID modulo 4 + 1) equals 1.

Assignment 1: Lamport clocks

Write a program that implements Lamport clocks.

Specifications

Command line interface:

```
program configuration_file line
```

where `configuration_file` is the name of the configuration file and `line` is the line of this client (see below).

The configuration file has an undetermined number of lines, each in the following format:

```
id host port
```

where `id` is an integer used in the manner described below, `host` is either the hostname or the IP address of the client and `port` is the port on which it is listening at that address. Your client program takes as argument one integer, which indicates its own ID, i.e., the line in the configuration that indicates what port this client should use. The client can ignore the hostname for its own line, but needs to use the other lines to know who are the other clients in the system. There is no upper limit to the number of lines in the configuration file. If the argument given to the program does not exist in the configuration file, your program is allowed to crash immediately.

NOTE: It's easiest to have all the clients run on the same machine during early development.

NOTE: You can develop your programs in any environment, but it must also be runnable on the Ukko cluster.

Running of the Program

Make sure all programs are running before having them start executing the algorithm. In the following, we use terms `node` and `program` interchangeably, since individual programs are intended to simulate different nodes.

Each node can freely choose to have either a local event or send a message to one other node. Choose randomly with equal probabilities between these two possibilities.

- For local event, increment local Lamport clock by a random amount selected uniformly at random between 1 and 5.
- For a message, select another node uniformly at random and send a message to that node with the correct clock value. The receiving node must execute Lamport's algorithm to update its clock correctly.

Every node should run for 100 events after which it is allowed to terminate. If a node happens to attempt to communicate with a departed node, have it fail in some graceful manner.

Output Format

Each individual program should produce an output of its run. Use the following syntax for output:

- Local event: $l \ n$, where n is the amount by which the clock was increased
- Sending a message: $s \ r \ l$, where r is the receiving node ID and l is the clock value sent in the message.
- Receiving a message: $r \ s \ t \ n$, where s is the sender of the message, t is the timestamp that was in the message, and n is the clock value after running Lamport's algorithm.

NOTE: Because we use partly automated tools for checking the output, your output must match exactly the format above. Do not add any other text or lines. Failure to comply will lead to a reduced grade.

Guidelines

You are free to choose any programming language, but we recommend using a higher level language, e.g., Ruby or Python, even if you have to learn the language from scratch during the assignment.

The actual contents of the messages are irrelevant, as long as you are able to implement the required functionality. No interoperability between groups is required so you are free to choose the format.

Deliverables

Program source code with documentation.

Timeline

The assignment is due on January 20th at 10:00. No extensions will be given.

Return

Return your code by email to Liang.Wang@cs.helsinki.fi as one tar-archive. Please indicate clearly your name and student ID in every source code file.